

COBRA® SPECIAL DESIGNS

ANCHOR COBRA OUL, OPENS UNDER LOAD

25 mm, 180 degrees rotatable

Art.no.: FO00K180-XL+L



Originally designed for Picatinny Arsenal as a conceptual MRAP anchoring system, the COBRA® ANCHOR OUL bolts (1/2 inch hardware) onto any solid surface. The female buckle portion of the anchor can be tilted by up 180 degrees offering a wide angle of use and variability. A COBRA® OUL (9 kN) male part is then affixed to any gear, kit, or package whereby it can be securely clipped in and stowed away for rapid, easy, safe access. This is great for vehicular and aircraft stowage applications as well as for applications where load bearing “clip and go” storage options are required. Not suitable as PPE!

use cases:

tactical, equipment

Technical specifications

BODY	Material: aluminium Color: black Finish: ktl-coated
CLIPS	Material: brass Color: colorless Finish: polished
PLATE	Material: aluminium Color: black Finish: ktl-coated
AXLE	Material: stainless steel Color: colorless Finish: polished
BREAKING LOAD TENSILE STRENGTH	9 kN
BREAKING LOAD LOOP CONFIGURATION	18 kN
WEIGHT	104 g
OUTER DIMENSION LENGTH	37 mm

OUTER DIMENSION WIDTH	40 mm
OUTER DIMENSION DEPTH	10 mm
WEBBING SLOT FEMALE PART	non-adjustable
SIZE OF CLIPS	XL
COUNTRY OF ORIGIN	Austria

**Patented**

