

## COBRA® PRO STYLE HYBRID

**45/25 mm**

Art.no.: FY4525KVF



The COBRA® PRO STYLE is the world leading safety buckle made of aluminium. Thanks to its patented locking mechanism and high breaking strength it meets the highest safety requirements. In combination with a fitting webbing, the minimum guaranteed load capacity is 9 kN tensile strength and 18 kN in loop configuration.

### Features:


- Both clips need to be pressed at the same time to open the COBRA®. One-sided release by pressing only one clip is nearly impossible.
- A release under tension is impossible.
- A one-sided locking is nearly impossible. Locking is confirmed by a distinct “clicking” sound.
- The cut-out on the backside of the COBRA® PRO STYLE prevents dirt, dust, ice or snow from getting caught in the buckle, which increases the extreme performance capabilities and lifetime even more.
- All sizes and variants of the COBRA® PRO STYLE are compatible.

### use cases:

equipment, Fashion, PPE, tactical

## Technical specifications

|   |  |
|---|--|
| <b>BODY</b>                             | <b>Material:</b> aluminium<br><b>Color:</b> black<br><b>Finish:</b> ktl-coated         |
| <b>CLIPS</b>                            | <b>Material:</b> brass<br><b>Color:</b> colorless<br><b>Finish:</b> polished           |
| <b>BAR</b>                              | <b>Material:</b> stainless steel<br><b>Color:</b> colorless<br><b>Finish:</b> polished |
| <b>BREAKING LOAD TENSILE STRENGTH</b>   | 9 kN   |
| <b>BREAKING LOAD LOOP CONFIGURATION</b> | 18 kN  |

|   |                                      |
|---|--------------------------------------|
| <b>WEIGHT</b>   | 66 g                                 |
| <b>RECOMM. WEBBING WIDTH MALE PART</b>  | 45 mm                                |
| <b>RECOMM. WEBBING WIDTH FEMALE PART</b>  | 25 mm                                |
| <b>SLOT WIDTH MALE PART</b>   | 12 mm                                |
| <b>SLOT WIDTH FEMALE PART</b>   | 4 mm                                 |
| <b>OUTER DIMENSION LENGTH</b>   | 63 mm                                |
| <b>OUTER DIMENSION WIDTH</b>  | 58 mm                                |
| <b>OUTER DIMENSION DEPTH</b>  | 10 mm                                |
| <b>WEBBING SLOT MALE PART</b>   | adjustable                           |
| <b>WEBBING SLOT FEMALE PART</b>   | non-adjustable                       |
| <b>SIZE OF CLIPS</b>  | standard                             |
| <b>COUNTRY OF ORIGIN</b>  | Austria                              |
|  <b>Patented</b> |                                      |
| <b>STANDARDS</b>  | EN358:2018-11 (partial), EN ISO 9227 |



