

COBRA® PRO STYLE ALUMINIUM

58 mm, XL clips, stretch

Art.no.: FY58KSS-XL



The COBRA® PRO STYLE is the strongest and world leading safety buckle made of aluminium. Thanks to its patented locking mechanism and high breaking strength it meets the highest safety requirements. In combination with a fitting webbing, the minimum guaranteed load capacity is 9 kN tensile strength and 18 kN in loop configuration.

This version of the COBRA® PRO STYLE is intended for 58 mm webbing width. The ergonomically designed brass clips of XL-size facilitate the opening of the buckle. Thanks to the adjuster bar on both parts of the buckle, no stitching is needed. The webbing length can be adjusted individually. In addition, the stretch version provides more space for thicker webbings.

Features:


- Both clips need to be pressed at the same time to open the COBRA®. One-sided release by pressing only one clip is nearly impossible.
- A release under tension is impossible.
- A one-sided locking is nearly impossible. Locking is confirmed by a distinct “clicking” sound.
- The cut-out on the backside of the COBRA® PRO STYLE prevents dirt, dust, ice or snow from getting caught in the buckle, which increases the extreme performance capabilities and lifetime even more.
- All sizes and variants of the COBRA® PRO STYLE are compatible.

use cases:

PPE, Fashion, air sports, tactical, equipment

Technical specifications

BODY	Material: aluminium Color: black Finish: ktl-coated
CLIPS	Material: brass Color: colorless Finish: polished

BAR	Material: stainless steel Color: colorless Finish: polished
BREAKING LOAD TENSILE STRENGTH	9 kN
BREAKING LOAD LOOP CONFIGURATION	18 kN
WEIGHT	107 g
RECOMM. WEBBING WIDTH MALE PART	58 mm
RECOMM. WEBBING WIDTH FEMALE PART	58 mm
SLOT WIDTH MALE PART	19 mm
SLOT WIDTH FEMALE PART	19 mm
OUTER DIMENSION LENGTH	89 mm
OUTER DIMENSION WIDTH	70 mm
OUTER DIMENSION DEPTH	10 mm
WEBBING SLOT MALE PART	stretch, adjustable
WEBBING SLOT FEMALE PART	stretch, adjustable
SIZE OF CLIPS	XL
COUNTRY OF ORIGIN	Austria
 Patented	
STANDARDS	, EN ISO 9227

