

## OVALO

### ID 2-WAY-AUTOLOCK

**aluminium, anodized**

Art.no.: KA22B-B-ID



OVALO – the yogi among the carabiners: Its oval form benefits the optimal position of the carabiner along its transverse axis and thus reduces dangerous transverse loading in every situation. Additionally, the round profile prevents the build-up of sharp edges due to rope friction and allows a fluid rope management. Special feature of the OVALO ID 2-way autolock is a unique identification number [ID]. To open: twist and push.


#### use cases:

sports climbing, ice climbing, mountain sports, canyoning, PPE


## Technical specifications

<b>BODY</b>	<b>Material:</b> aluminium <b>Color:</b> azure <b>Finish:</b> anodized
<b>GATE</b>	<b>Material:</b> aluminium <b>Color:</b> black <b>Finish:</b> anodized
<b>SLEEVE</b>	<b>Material:</b> aluminium <b>Color:</b> colorless <b>Finish:</b> anodized
<b>WEIGHT</b>	67 g
<b>LENGTH</b>	105 mm
<b>WIDTH</b>	56 mm
<b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b>	24 kN
<b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>	10 kN
<b>MIN. BREAKING LOAD WITH OPEN GATE</b>	7 kN


<b>LOCK</b>	2-way autolock
<b>FEATURES</b>	ID
<b>GATE OPENING</b>	18 mm
<b>COUNTRY OF ORIGIN</b>	Austria
<b>EAN CODE</b>	9006381024407
<b>STANDARDS</b>	EN 12275:2013 (B), EN 362:2004 (B), UIAA 121



**UNIQUE IDENTIFICATION NUMBER (ID)**



— ID# KA 01234 letter 1 and 2 of article no. / unique number

—  XX/XXXX month/year of production

— EN 362-B additional norm marking