

## D ASYMM

### 3-WAY AUTOLOCK

stainless steel 40 kN, with splint

Art.no.: TN35AK3-IS



Strong carabiner shape with 3-way autolock and splint, made of stainless steel. To open: lift, twist and push.

#### use cases:

PPE, equipment

## Technical specifications

|   |  |
|---|--|
| <b>BODY</b>   | <b>Material:</b> stainless steel<br><b>Color:</b> colorless<br><b>Finish:</b> polished |
| <b>GATE</b>   | <b>Material:</b> stainless steel<br><b>Color:</b> colorless<br><b>Finish:</b> polished |
| <b>SLEEVE</b>                                       | <b>Material:</b> brass<br><b>Color:</b> colorless<br><b>Finish:</b> polished           |
| <b>SAFETY PIN</b>                                   | <b>Material:</b> stainless steel<br><b>Color:</b> colorless<br><b>Finish:</b> polished |
| <b>WEIGHT</b>                                       | 257 g  |
| <b>LENGTH</b>                                       | 113 mm   |
| <b>WIDTH</b>  | 70 mm  |
| <b>MIN. BREAKING LOAD IN LONGITUDINAL DIRECTION</b> | 40 kN  |
| <b>MIN. BREAKING LOAD IN THE MINOR AXIS</b>         | 16 kN  |
| <b>MIN. BREAKING LOAD WITH OPEN GATE</b>            | 12 kN  |

|                          |  |
|--------------------------|--|
| <b>LOCK</b>              | 3-way autolock                               |
| <b>GATE OPENING</b>      | 25 mm  |
| <b>COUNTRY OF ORIGIN</b> | Austria                                      |
| <b>EAN CODE</b>          | 9006381007929                                |
| <b>STANDARDS</b>         | EN 12275:2013 (B), EN 362:2004 (M), UIAA 121 |

